

Emergency illumination

LED Light Fixture

IP65

Spektr-Em-BA



- Public spaces,
- offices,
- halls,
- trading floors.

Basic parameters of LED light fixture


Product name	Light flux in standard operating/emergency mode, lm	Power consumption, W	IP degree	Overall dimensions, mm	Weight, kg
Spektr-Em-BA (SSOR-A-220-050-N-MCC1)	4500/500	60	IP65	635x180x110	2,1

Spektr-Em-BA can work in both standard operating and emergency modes.

General parameters of LED light fixture

AC Supply voltage, V	from 140 to 265
Frequency, Hz	50±10%
Installation type	surface-mounted
Operating temperature range, °C	from - 0 to + 50
Emission color	white
Color temperature of emission, K	N - 4500÷5500
Climatic performance according to State Standard 15150	MCC1
Electric shock protection class in accordance with IEC 60598-1, part 8	I
Operating hours in emergency service, hours	1
Battery unit type	built-in
Warranty, years	5
Durability, hours	100000

Light Distribution Curve



A - cosine

Overall dimensions of LED light fixture	Installation type of LED light fixture
	<p>Installation on tension cables is possible</p>



JSC «Proton», 302040, Orel, Leskova str., 19, tel./fax: (4862) 41-44-03
www.proton-orel.ru