

LED Light Fixture

IP67

Avenue series



Outdoor illumination



- Highways,
- streets and roads,
- side-walks,
- railway platforms,
- crosswalks,
- parking lots,
- petrol stations.

Basic parameters of LED light fixture


Product name	Light flux, lm	Power consumption, W	IP degree	Overall dimensions (AxBxC), mm	Weight, kg
Avenue-30 (SKSR-A/B/C-220-001-N/W-MCC1)	3750	30	IP67	245x209x105	3,2
Avenue-60 (SKSR-A/B/C-220-002-N/W-MCC1)	7500	60		340x209x105	5,5
Avenue-90 (SKSR-A/B/C-220-003-N/W-MCC1)	11250	90		462x209x105	7,5
Avenue-120 (SKSR-A/B/C-220-004-N/W-MCC1)	15000	120		580x209x105	9,7
Avenue-150 (SKSR-A/B/C-220-005-N/W-MCC1)	18750	150		720x209x105	11,3
Avenue-180 (SKSR-A/B/C-220-006-N/W-MCC1)	22500	180		840x209x105	13,2
Avenue-180D (SKSR-B-220-017-N/W-MCC1)	22500	180		840x209x105	13,2

Avenue-180D has an ability to adjust light flux value from 10% to 100% by the outside control voltage from 0 V to 10 V.


General parameters of LED light fixture

AC supply voltage, V	from 140 to 265
Frequency, Hz	50 ± 10%
DC supply voltage, V	from 200 to 370
Operating temperature range, °C	from - 63 to + 60
Emission color	white
Color temperature of emission, K	W - 3000÷4000/N - 4000÷6000
Climatic performance in accordance with State Standard 15150	MCC1
Warranty, years	5
Durability, years	10


Light Distribution Curve



A - cosine



B - wide



C - deep

Overall dimensions of LED light fixture

