

LED Light Fixture

Street series

IP65



Outdoor illumination



- Streets and roads,
- side-walks,
- railway platforms,
- crosswalks,
- parking lots,
- petrol stations.



Basic parameters of LED light fixture

Product name	Light flux, lm	Power consumption, W	IP degree	Overall dimensions, mm	Weight, kg
Street-30 (SSOR-A-220-003-N/W-MCC1)	3250	26	IP65	310x180x107	3,0
Street-50 (SSOR-B-220-004-N/W-MCC1)	7440	62		635x180x107	5,5
Street-70 (SSOR-A-220-010-N/W-MCC1)	11250	90		715x180x107	6,0
Street-100 (SSOR-B-220-005-N/W-MCC1)	15000	125		1228x180x107	10,0


General parameters of LED light fixture

AC supply voltage, V	from 140 to 265
Frequency, Hz	50±10%
DC supply voltage, V	from 200 to 370
Operating temperature range, °C	from - 40 to + 60
Emission color	white
Color temperature of emission, K	W- 3000÷4000/N- 4000÷6000
Climatic performance in accordance with State Standard 15150	MCC1
Warranty, years	5
Durability, years	10


Light Distribution Curve



A – cosine
(Street-30)



A – cosine
(Street-70)



B – wide
(Street-100)

Overall dimensions of LED light fixture	Installation type of LED light fixture