

## Small size double LED beacon of low intensity ZOM PPM C-R-48-2A

**LED Beacon** of type «ZOM PPM C-R-48-2A» is a double beacon of low intensity and designed for the light marking high and extensive buildings. **Specially designed LED** are used in this beacon. It provides **optimal emission diagram and luminous intensity**, which meet the requirements of **ICAO and FAA**, and high reliability of the device.

Double LED beacon consists of two lights fixed on contacting surface and set on the mast with the diameter of  $\frac{3}{4}$  inches of high or extensive structures. Power supply cable connection is performed to the contacting surface of light device.

### Specifications

Warranty period is 5 years;

Lifetime: not less than 12 years

Voltage supply: non polar: 48 V (42-60 ) DC;

Power consumption: not more than 9 W;

Emission colour: red;

Luminous intensity in a vertical surface  $+6^{\circ} \div +10^{\circ}$ : not less 32 cd (ICAO type «C»)

Luminous intensity in a vertical surface  $-6^{\circ} \div +50^{\circ}$ : not less 4 cd;

Emitting angle in a horizontal surface:  $360^{\circ}$ ;

Climatic performance: MCC 1;

Protection extent: IP54;

Colour filter: colourless, transparent;

Package and colour filter material: shockproof polycarbonate.



LED beacon outward